


FLAT SLIM round

312644.002.1.76 | Pendant luminaires



Pendant luminaires
4051859802266
D 400, H 70

pendant
traffic white, matt (RAL 9016)



Decorative round LED pendant luminaire. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Canopy made of aluminium, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: bayonet system. Uniform lighting achieved by the use of LED panel boards. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. MultiLumen: 2 steps adjustable luminous flux. Factory setting is the highest luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K via switching element. Factory setting is 3000 K. Dimmable DALI.

Product specifications


Diameter D	400 mm
Height H	70 mm
Suspension length LP	500-1500 mm
Weight	5.2 kg
Light source	LED
Colour temperature	3000 K 4000 K
Rated luminous flux	3000 K: 2450 lm 4000 lm 4000 K: 2500 lm 4100 lm
System power	3000 K: 18 W 29 W 4000 K: 18 W 29 W
System efficiency	3000 K: 136 lm/W 138 lm/W 4000 K: 139 lm/W 141 lm/W
Glare evaluation UGR (4H 8H)	3000 K: 22,5 24,2 4000 K: 22,6 24,3
Beam angle	down 142° up 180°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	12
Luminaires on B16A fuse	20
Luminaires on C10A fuse	21
Luminaires on C16A fuse	34
Inrush current / Inrush current duration	21 A / 230 µs
CIE Flux Code / CEN Flux Code	37 67 88 84 100
Protection class	I
Filament test	850 °C
Impact resistance	IK08
Ambient temperature	-25 °C ... + 40 °C
Conformity mark	CE, EAC

FLAT SLIM round

312644.002.1.76 | Pendant luminaires



Spareparts



982972.002
Replacement LED module



982896.002
Replacement diffuser