

PRODUCT DATASHEET

Renovation Lamp Classic A75 Terminal Block 10W 840 Triple Pack

RENOVATION LAMPS WITH TERMINAL BLOCK | LED lamp with a terminal block for direct connection to the ceiling or wall at construction sites or for moving



Areas of application

- New construction sites or apartments and houses for temporary light
- Practical temporary light for indoor ceiling or wall installation
- For indoor use only

Product benefits

- Ideal light for construction sites, renovations, or moving
- Can be easily and quickly fitted
- Offered in a closed box, the integrated terminal block ensures safe installation on the wall or ceiling

Product features

- The lamp has an integrated power cable, including the terminal block
- The lamp can be directly connected to AC 220-240V without a socket
- A strong lumen output with 1050 lm at 4000K provides bright and energy efficient light
- The light source is not replaceable



TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Nominal voltage	220...240 V
Nominal current	70.000 mA
Type of current	AC
Inrush current	6.4 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.5


Photometrical data

Luminous flux	1055 lm
Luminous efficacy	105 lm/W
Light color (designation)	Cool white
Color temperature	4000 K
Color rendering index Ra	> 80
Light color	840
Standard deviation of color matching	≤6 sdc _m
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4

Light technical data

Beam angle	200 °
------------	-------

Dimensions & Weight



Diameter	60.00 mm
----------	----------

Product weight	55.00 g
----------------	---------

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
---------------------------	---------

Additional product data

Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Available from February 2025

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1

Country-specific categorizations

Order reference	RENOVATION CLA7
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Length	98.00 mm
Height	291.00 mm
Width	60.00 mm




EQUIPMENT / ACCESSORIES

- Integrated 13-cm long power cable and the terminal block in closed box

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	RENOV Lamp UI
	Declarations of conformity	Luminares
	Declarations of conformity UKCA	Luminaries

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854421471	Folding box 3	62 mm x 62 mm x 162 mm	130.00 g	0.62 dm ³
4099854421488	Shipping box 30	343 mm x 193 mm x 249 mm	2063.00 g	16.48 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.