FLAT SLIM round


312630.004.1 | Ceiling and wall luminaires





Ceiling and wall luminaires 4051859772194 D 300, H 70

Ceiling mounting, Wall (surface) silver, matt (approx. RAL 9006)



Decorative round LED surface-mounted luminaire for indoor and outdoor use. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: bayonet system. Uniform lighting achieved by the use of LED panel boards. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug & play connection. The large connection compartment on the back for convenient connections is also ideal for through wiring. MultiLumen: 2 steps adjustable luminous flux. Factory setting is the highest luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K via switching element. Factory setting is 3000 K.

Product specifications

Product specifications		
Diameter D	300 mm	
Height H	70 mm	
Weight	1.6 kg	
Light source	LED	
Colour temperature	3000 K 4000 K	
	3000 K: 1450 lm 2400 lm	
Rated luminous flux	4000 K: 1450 lm 2450 lm	
	3000 K: 11 W 17 W	
System power System officions/	4000 K: 11 W 17 W	
	3000 K: 132 lm/W 141 lm/W	
System efficiency	4000 K: 132 lm/W 144 lm/W	
Glare evaluation UGR (4H 8H)	3000 K: 22,4 24,1 4000 K: 22,4 24,2	
Giare evaluation out (411 ori)	down 137°	
Beam angle	up 180°	
Rated life	50000 h (L90/B50)	
Colour rendering index (CRI)	80	
Colour tolerance	3	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter	
Control	on/off	
Voltage	220 - 240 V / 50 Hz, 60 Hz	
Luminaires on B10A fuse	31	
Luminaires on B16A fuse	50	
Luminaires on C10A fuse	52	
Luminaires on C16A fuse	85	
Inrush current / Inrush current duration	5 A / 50 μs	
CIE Flux Code / CEN Flux Code	38 68 88 84 100	
Type of protection	IP 65	
Protection class		
Filament test	850 °C	
Impact resistance	IK08	
Ambient temperature	-25 °C + 35 °C	
Safety marks	D-mark	
Conformity mark	CE, EAC	

FLAT SLIM round

312630.004.1 | Ceiling and wall luminaires



Spareparts



982971.002 Replacement LED module



982894.002 Replacement diffuser