

# TRIONA rectangle

312715.002.76 | Surface-mounted luminaires



Ceiling and wall luminaires  
4051859966111  
L 1560, B 350, H 88

Ceiling mounting, Wall (surface)  
traffic white, matt (RAL 9016)



Decorative rectangular LED surface-mounted luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Diffuser made of non-yellowing plastic (PMMA) microprismatic. LED backlight technology for homogeneous illumination of the entire light-emitting surface. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug & play connection. Driver integrated. Dimmable DALI. Suitable for through-wiring.

## Product specifications

|                                              |                            |
|----------------------------------------------|----------------------------|
| Length L                                     | 1560 mm                    |
| Width B                                      | 350 mm                     |
| Height H                                     | 88 mm                      |
| Weight                                       | 15 kg                      |
| Light source                                 | LED                        |
| Colour temperature                           | 3000 K                     |
| Rated luminous flux                          | 6250 lm                    |
| System power                                 | 49 W                       |
| System efficiency                            | 128 lm/W                   |
| Glare evaluation UGR (4H 8H)                 | 18,7                       |
| Beam angle                                   | 93°/94°                    |
| Rated life                                   | 50000 h (L80/B10)          |
| Colour rendering index (CRI)                 | 80                         |
| Photobiological safety according to EN 62471 | Risk group 1               |
| Driver                                       | Converter, dimmable        |
| Control                                      | DALI                       |
| Voltage                                      | 220 - 240 V / 50 Hz, 60 Hz |
| Luminaires on B10A fuse                      | 12                         |
| Luminaires on B16A fuse                      | 20                         |
| Luminaires on C10A fuse                      | 21                         |
| Luminaires on C16A fuse                      | 33                         |
| Inrush current / Inrush current duration     | 20 A / 200 µs              |
| CIE Flux Code / CEN Flux Code                | 60 87 97 100 100           |
| Type of protection                           | IP 20                      |
| Protection class                             | I                          |
| Filament test                                | 650 °C                     |
| Impact resistance                            | IK03                       |
| Ambient temperature                          | -20 °C ... + 35 °C         |
| Conformity mark                              | CE                         |