


# FLAT SLIM round

312135.0031.2.191 | Ceiling and wall luminaires



Ceiling and wall luminaires  
4051859183471  
D 230, H 63

Ceiling mounting, Wall (surface)  
anthracite metallic (DB703)



Decorative round LED surface-mounted luminaire for indoor and outdoor use. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: bayonet system. Uniform lighting achieved by the use of LED panel boards. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug & play connection. The large connection compartment on the back for convenient connections is also ideal for through wiring. Slave luminaire. Can only be operated in combination with corresponding master luminaire.

## Product specifications

Diameter D	230 mm
Height H	63 mm
Weight	1.1 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	1300 lm
System power	13 W
System efficiency	100 lm/W
Glare evaluation UGR (4H 8H)	23
Beam angle	down 119° up 180°
Rated life	50000 h (L70/B10)
Colour rendering index (CRI)	83
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Not necessary
Control	on/off
Voltage	220 - 230 V / 50 - 60 Hz
Luminaires on B10A fuse	114
Luminaires on B16A fuse	182
Luminaires on C10A fuse	114
Luminaires on C16A fuse	182
Inrush current / Inrush current duration	0.15 A / 10000 µs
CIE Flux Code / CEN Flux Code	43 74 92 91 100
Type of protection	IP 65
Protection class	I
Impact resistance	IK08
Ambient temperature	-20 °C ... + 30 °C
Conformity mark	CE, EAC

## Spareparts



983180.002  
Replacement diffuser



E90-6843.000