


MEGA TUBE

621102.0231.1 | Wall luminaires



Wall luminaires
4051859512325
L 160, B 115, H 338

Wall (surface)
anthracite metallic (DB703)



Attractive wall luminaire with innovative housing design and high-quality LED optics. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Light emission: downwards. Flood. Switchable separately. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravalock® System. Connection box on base, max. 2 x 5 x 2.5 mm² for loop through.

Product specifications

Length L	160 mm
Width B	115 mm
Height H	338 mm
Weight	3.1 kg
Light source	LED
Colour temperature	#4000 K #4000 K
Rated luminous flux	830 lm
System power	14 W
System efficiency	59 lm/W
Glare evaluation UGR (4H 8H)	18,4
Beam angle	down 45°/36°/26°/36° up 90°/90°/90°/90°
Rated life	60000 h (L80/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
Luminaires on B10A fuse	39
Luminaires on B16A fuse	63
Luminaires on C10A fuse	63
Luminaires on C16A fuse	100
Inrush current / Inrush current duration	8 A / 5 µs
CIE Flux Code / CEN Flux Code	42 59 79 55 100
Type of protection	IP 65
Protection class	I
Filament test	960°C - 30 seconds
Impact resistance	IK04
Ambient temperature	-20 °C ... + 45 °C
Conformity mark	CE, EAC

MEGA TUBE

621102.0231.1 | Wall luminaires



Spareparts



982108.0131
Replacement glass