

DEEP

RECESSED PANEL

STH8902PTO/30

Power

750lm

Luminous flux


120°

Beam angle




Technical Drawing

STH8902




Graphics

STH8902PTO

h, E_{max}, Ø

STH8902PTO



C0/80 C90/270

TECHNICAL SPECIFICATIONS TABLE

Beam angle	120°
Luminous efficacy	63lm/W
Power factor	0,5
Luminous flux	750lm
Frequency	50/60Hz
CRI (Color rendering index)	80
Correlated color temperature (CCT)	3000K
Operation temperature	-10°C ~ 40°C
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

OTHER INFORMATION

Finishing	Black
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

[↓ IES FILE - STH8902PTO/30](#)
[↓ MANUAL DEEP](#)
[↓ SKETCHUP - STELLA - STH8902BR-30-40-50 - STH8902PTO-30-40 - PAINEL DE EMBUTIR RECUADO DEEP 12W_PACK.zip](#)
[↓ REVIT - STH8902BR_30_40_50_STH8902PTO_30_40.rfa](#)
