



MASTER VALUE LEDspot MV

MASTER LED spot VLE D 2.8–35W GU10 927 60D

Delivering a warm, halogen-like accent beam, MASTER LEDspot MV is a perfect fit for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suitable to public areas where the light is on 24/7, such as lobbies, corridors, stairwells. MASTER LEDspot MV delivers huge energy savings and minimizes maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. These LEDspots are compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement for halogen or incandescent spots. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	GU10
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Narrow Cone
Light Technical	
Color Code	927 [CCT of 2700K]

Beam Angle (Nom)	60 degree(s)
Luminous Flux	270 lm
Luminous Intensity (Nom)	300 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	96 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %

MASTER VALUE LEDspot MV

Luminous Flux in 90° Cone (Rated)	270 lm
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Input Frequency	50 to 60 Hz
Power Consumption	2.8 W
Lamp Current (Nom)	21 mA
Wattage Equivalent	35 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	50 °C
----------------------	-------

Controls and Dimming

Dimmable	Only with specific dimmers
----------	----------------------------

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	PAR16
Net Weight (Piece)	0.041 kg

Approval and Application

Energy Efficiency Class	E
Suitable For Accent Lighting	Yes

Energy Consumption kWh/1000 h	3 kWh
EPREL Registration Number	2150468
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

Product Data

Order product name	MAS LED spot VLE D 2.8-35W GU10 927 60D
Full product name	MASTER LED spot VLE D 2.8-35W GU10 927 60D
Full product code	872016939916700
Order code	39916700
Material Nr. (12NC)	929004247602
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169399167
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169399174



Dimensional drawing



Product	D	C
MAS LED spot VLE D 2.8-35W GU10 927 60D	50 mm	54 mm


MASTER VALUE LEDspot MV

Photometric data



Accent Lighting Spots - MAS LED spot VLE D 2.8-35W GU10 927 60D

Light Distribution Diagram - MAS LED spot VLE D 2.8-35W GU10 927 60D



Spectral Power Distribution Colour - MAS LED spot VLE D 2.8-35W GU10 927 60D

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LED spot VLE D 2.8-35W GU10 927 60D

MASTER VALUE LEDspot MV

