

DLN 220 LED EVO LV 220MM 3200LM 830 PRM (28W) INW

DETAILED CARD



TECHNICAL PARAMETERS

Index:	554445
Ingress protection:	IP65
Nominal power [W]:	28
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	powder coated steel
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

Surface-mounted downlight with an integrated energy-saving LED panel, with high ingress protection class IP65 and high impact protection class IK08. Opal diffuser made of polycarbonate ensures even light distribution.

APPLICATION

The fitting is intended for surface mounting. High ingress protection class IP65 and high impact protection class make it suitable for outdoor use. Small parameters and timeless design will also prove useful in offices, passageways and administrative buildings.

DLN 220 LED EVO LV 220MM 3200LM 830 PRM (28W) INW

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	Mounting dimensions [mm]:	ø90
Light source:	LED module	Impact resistance:	IK08
Colour temperature [K]:	3000	Ingress protection:	IP65
Rated power of the luminaire [W]:	29.30	Mounting version:	surface
Diffuser type:	PRM	Working temperature [°C]:	from -15 to +35
Supply voltage [V]:	220-240	Net weight [kg]:	1.660
Luminous efficacy [lm/W]:	109	Gross weight [kg]:	2.550
Energy efficiency class:	D	Index:	554445
Electrical protection class:	I	EAN:	5905963554445
Colour rendering index:	>80	Category type:	downlights
SDCM:	≤ 3	Luminaire rated power P_{min} [W]:	30.40
Power factor:	0.96	LED lifespan L80B20 [h]:	73000
LED lifespan L70B50 [h]:	117000	LED lifespan L90B10 [h]:	34000
Beam angle [°]:	120	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Warranty [years]:	5
Diffuser colour:	transparent	CE certificate:	333/2023
Material of the body:	powder coated steel	ENEC Certificate:	0346/ENEC/24
Colour of the body:	grey	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	ø220/140	Plik LDT:	Download

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 333/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl