

CAPELLA LED PLUS PRO TS IOT BT DS HYT DALI 1400LM 830 IP54 WHITE (15W) 320MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	951282
Ingress protection:	IP54
Impact resistance:	IK06
Nominal power [W]:	15
Luminous flux [lm]*:	1400
Colour temperature [K]:	3000
SDCM:	≤ 4
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Capella LED Plus IoT is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications. **IoT characteristics** The **IoT BT DS HYT DALI** version has: a built-in **BT HYT** module that allows you to program functions in the Lena Lighting Clue app and control in real time; **DS** daylight sensor hidden under the shade and **DALI** driver for dimming the light source.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


CAPELLA LED PLUS PRO TS IOT BT DS HYT DALI 1400LM 830 IP54 WHITE (15W) 320MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	Colour of the body:	white
Index:	951282	Ring material:	ABS
Colour temperature [K]:	3000	Ring colour:	white
EAN:	5905963951282	Dimensions (H/W/T/S) [mm]:	320/105
Luminous flux [lm]:	1400	Mounting dimensions [mm]:	158
Light source:	LED module	Impact resistance:	IK06
Rated power of the luminaire [W]:	16.50	Ingress protection:	IP54
Supply voltage [V]:	220-240	Mounting version:	surface
Master/slave:	slave	Working temperature [°C]:	from -10 to +35
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous efficacy [lm/W]:	86	Version:	BT DS HYT DALI
Energy efficiency class:	F	Accessories included:	assembly system for IoT, sealing, extraction, 2x cable cover, screws, dowels 6mm
Electrical protection class:	II	Dimensions of single box [mm]:	342/342/122
Colour rendering index:	>80	Net weight [kg]:	0.920
SDCM:	≤ 4	Category type:	bulkheads
Power factor:	0.95	AC voltage range [V]:	220 - 240
LED lifespan L70B50 [h]:	30000	UGR (4H8H):	17,5-25,2
Beam angle [°]:	120	Light distribution type:	labertowski
Diffuser material:	PC	Product line:	PRO
Diffuser type:	OPAL	Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics material:	PMMA	Warranty [years]:	5
Optics:	lens	CE certificate:	375/2023
Material of the body:	ABS	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES



Card creation date: 10 March 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 375/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl